





Projector equipped with an LED board
Light efficiency of the complete system 116lm/W
Maintenance of L90F10 flux greater than 100,000 hours (Ta25°C)
Die-cast aluminum body promoting passive cooling with anti-UV treatment
Translucent tempered glass diffuser
Optional asymmetrical lens with 90x150°aperture beam
Ideal for lighting stadiums, tunnels, bridges, airports, amusement parks, etc.
70cm output cable

Mechanical Features



Colour	Black		
Body	Aluminum die cast		
Diffuser	Glass		
Installation	Applied		
Immersion	No	Recoverable	No
IP Wall Lamp	65	Incandescent wire T°	650°C
Luminaire width	236mm	IK	08
		Luminaire length	293mm
		Luminaire height	47mm
		Fixing dimensions	50mm

Electrical Features




Voltage range	220-240V/50-60Hz		
Luminaire wattage	19.5W		
Number of lamps	1		
Ta min/max	-40°C/80°C		
Carbon footprint	1.75 gCO2/h		
Luminaire number type B	10A	16A	25A
	85	140	200
Luminaire number type C	110	160	320



Photometric Features

Colour Temperature	3000K
Lamp type	LED module
Output flow to 25°C Ta	2270lm
Lighting efficiency for the whole product	116lm/W
Light output (LOR)	100%
Light emission	Direct/Symetrical
Beam angle	104°
Diffuser	Translucent
Photobiological risk	Risk group 0
LM80	L90F10 > 100 000h (Ta25°C)
CIE flux code n°3 (%)	99%
ULR	1%

This fixture is not suitable for accent lighting.



This product contains an energy efficient light source

D

Normative Features

PEP Availability upon request

The technical features can be changed by RESISTEX without notice. Information subjected to error.