





Projector equipped with an LED board
Light efficiency of the complete system 127lm/W
Maintenance of L90F10 flux greater than 100,000 hours (Ta25°C)
Three adjustment levels: 100W (130lm/W / 120W (127lm/W) / 150W (144lm/W)
Die-cast aluminum body promoting passive cooling with anti-UV treatment
Luminaire equipped with an asymmetrical lens
Driver integrated directly into the luminaire
70cm output cable

Mechanical Features



Colour	Black		
Body	Aluminum die cast		
Diffuser	Glass		
Installation	Applied		
Immersion	No	Recoverable	No
IP Wall Lamp	65	Incandescent wire T°	650°C
Adjustability	Adjustable	IK	08
Luminaire width	319mm	Luminaire length	435mm
		Luminaire height	610mm
Fixing dimensions			13mm

Electrical Features




Voltage range	220-240V/50-60Hz		
Luminaire wattage	117.9W		
Number of lamps	1		
Ta min/max	-40°C/80°C		
Lamp supply	Constant current driver		
Input signals	AC		
Carbon footprint	10.61 gCO2/h		
Luminaire number type B	10A	16A	25A
	3	6	9
Luminaire number type C	6	10	15
Short circuit protection	Yes	Overheat protection	Yes
Overload protection	Yes	Protection surtension	Yes

Photometric Features

Colour Temperature	3000K
Lamp type	LED module
Output flow to 25°C Ta	15055lm
Lighting efficiency for the whole product	127.69lm/W
Light output (LOR)	100%
Light emission	Direct/Symetrical
Beam angle	158°
Diffuser	Translucent
Photobiological risk	Risk group 0
Maintaining flow	L90F10 > 100 000h (Ta25°C)
CIE flux code n°3 (%)	97%
ULR	2%
SVM	0.005
PstLm	0.032

This fixture is not suitable for accent lighting.



This product contains an energy efficient light source

E

Normative Features

Certificate of energy saving	BAT-EQ-127 / RES-EC-104	PEP	Availability upon request
------------------------------	-------------------------	-----	---------------------------

The technical features can be changed by RESISTEX without notice. Information subjected to error.

