





Recessed linear luminaire equipped with high performance LEDs
Light efficiency of the complete system 126lm/W
Maintenance of L80F10 flow greater than 54,000 hours (Ta 25°C)
Promotes a UGR <16 with a wide and uniform beamwidth of 80°
Black reflector designed to cut the luminous flux from 150°to 180 WWW: optimal visual comfort
Thickness and quality of aluminum dimensioned for excellent temperature management
Remote constant current driver
Tailor-made projects, personalized solutions ready to install

Mechanical Features



Electrical Features




Colour	White		
Body	Extruded aluminum		
Reflector	Polycarbonate		
Installation	Ceiling recessed		
Immersion	No	Recoverable	No
IP Recessed	20	Incandescent wire T°	650°C
Adjustability	Fixed	IK	06
Luminaire width	66mm	Luminaire length	1015mm
Cutting length	1000mm	Luminaire height	36mm
embedment depth	34mm		
		Cutting width	48mm

Voltage range	220-240V/50-60Hz		
Luminaire wattage	35.5W		
Lamp wattage	34W		
Driver Output	89%		
Ta	25°C		
Tc	90°C		
Lamp supply	Constant current driver		
Input signals	AC		
Driver output tension	3-42V		
Ampere exit driver	1000mA		
Wattage factor/cosφ	0,97		
Carbon footprint	3.19 gCO2/h		

	10A	16A	25A
Luminaire number type B	-	38	-
Luminaire number type C	-	45	-
Short circuit protection	Yes	Overheat protection	Yes
Overload protection	Yes		

Photometric Features

Colour Temperature	4000K
Lamp type	LED module
Light source efficiency	132lm/W
Output flow to 25°C Ta	4484lm
Lighting efficiency for the whole product	126lm/W
Light output (LOR)	100%
Light emission	Direct/Symetrical
Beam angle	80°
Diffuser	Translucent
CRI	83
Photobiological risk	Risk group 0
Number of MacAdam's ellipses	<3 SDCM
4000K coordinates	x : 0.3867; y : 0.3835
UGR type	<16
LM80	L80F10 > 54000h (Ta25°C)
CIE flux code n°3 (%)	100%
ULR	0%
SVM	0.005
PstLm	0.004



This product contains an energy efficient light source

D

Normative Features

PEP	Availability upon request
-----	---------------------------

The technical features can be changed by RESISTEX without notice. Information subjected to error.